

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
10 March 2005 (10.03.2005)

PCT

(10) International Publication Number  
**WO 2005/021878 A1**

(51) International Patent Classification<sup>7</sup>: E02F 3/88 // 3/92

(74) Agent: CURO AS; Box 38, N-7231 Lundamo (NO).

(21) International Application Number:

PCT/NO2004/000255

(22) International Filing Date: 30 August 2004 (30.08.2004)

(25) Filing Language: Norwegian

(26) Publication Language: English

(30) Priority Data:

20033872 1 September 2003 (01.09.2003) NO

(71) Applicant (for all designated States except US): FOS-  
SURA AS [NO/NO]; Leira, N-6590 Tustna (NO).

(72) Inventors; and


(75) Inventors/Applicants (for US only): JACOBSEN, Tom  
[—/NO]; Oscar Wistings v. 54, N-7020 Trondheim (NO).  
SNELLINGEN, Halvor [NO/NO]; Tunby, N-1820 Spy-  
deberg (NO).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: SUBSEA EXCAVATION AND SUCTION DEVICE



(57) Abstract: Subsea excavation and suction device comprising a suction head (1) with an inlet opening (3) at an outer, free end and an outlet opening (12) connected to a suction hose (10) arranged at a distance from the inlet opening (3). The suction head (1) is mounted on a hydraulic controller arm (13) and has at the inlet opening (3) provided with mechanic and hydraulic means to disintegrate solid material (sediment). The hydraulic means comprise a number of jet nozzles (7) while the mechanic means comprise bars (4, 5). The cross-sectional area of the inlet opening (3) is larger than the cross-sectional area of the outlet opening (12).



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*